

<b>Category</b>	UTP Patch Panel
<b>Specification</b>	RJ-45 Cat-5E, Cat-6 or Cat-6A UTP Patch Panel
<b>Parameters</b>	<p><b>Panel Type</b> : Angled or Flat Panel</p> <p><b>Cable Type</b> : Cat-5E, Cat-6 or Cat-6A</p> <p><b>Panel Materials / Color</b> : Sheet metal with black powder coating</p> <p><b>Overall Dimensions (H x W x D):</b></p> <ul style="list-style-type: none"> <li>• 1U Flat Panel : 44mm X 482mm X 270 mm</li> <li>• 2U Flat Panel : 88mm X 482mm X 270 mm</li> <li>• 1U Angled Panel : 44mm X 482mm X 150 mm</li> <li>• 2U Angled Panel : 88mm X 482mm X 150 mm</li> </ul> <p><b>Port Density</b> :</p> <ul style="list-style-type: none"> <li>• 1U : 24-port</li> <li>• 2U : 48-port</li> </ul> <p><b>Weight (Kg):</b></p> <ul style="list-style-type: none"> <li>• 1U Flat Panel : 1.0 Kg</li> <li>• 2U Flat Panel : 1.8 Kg</li> <li>• 1U Angled Panel : 0.9 Kg</li> <li>• 2U Angled Panel : 0.7 Kg</li> </ul> <p><b>Jack Module:</b> RJ-45</p> <p><b>Acceptable Conductor Range</b> : 22 ~ 26AWG</p> <p><b>Terminations:</b> 110 Punchdown style</p> <p><b>Durability</b> : 1500 mating</p> <p><b>Operation Temperature</b> : - 40°C ~ +60°C</p>

Specifications are subject to change without notice.

<b>Category</b>	UTP Patch Panel
<b>Specification</b>	RJ-45 Cat-5E, Cat-6 or Cat-6A UTP Patch Panel
<b>Parameters</b>	<p><b>Compliance :</b></p> <ul style="list-style-type: none"> <li>• For Cat-5E patch panels: complies ANSI/TIA-568A for Category 5E requirements</li> <li>• For Cat-6 patch panels : complies ANSI/TIA-568 for Category 6 requirements</li> <li>• For Cat-6A patch panels : complies ANSI/TIA-568-B2.0 for Category 6A requirements</li> <li>• ANSI/TIA-1096-A</li> <li>• RoHS</li> <li>• UL 94 V-1</li> <li>• ETL Tested</li> <li>• IEEE 802.3an</li> <li>• ISO/IEC 11801 Ed.2.2</li> </ul>

Specifications are subject to change without notice.