


# HD MPO CASSETTE MODULES

High Density snap-in MPO Cassette preloaded with 72-Fiber MPO to LC hydra assemblies.

Use to house into Olabs' plug-and-play high density rackmount enclosure (in Page 98), it supports high density plug-and-play system for improving cable manageability and quick installation.

Options of 6x12F MPO or 3x24F MPO to cater for different cable management needs.



## KEY FEATURES :


- Integrated with Olabs High Density Plug-and-Play Enclosures
- 72-Fiber per cassette by using 6x12F or 3x24F MPO connector for options
- MPO pinned (Male) with customer specified fiber mode and channel polarity
- User friendly snap-in modular cassette design
- Reduce labour cost by eliminating field terminations
- Pre-installed with factory-terminated MPO to LC hydra assemblies

## Specifications

<b>Main Material</b>	Standard offer : Steel Option for Aluminum upon request
<b>Dimension</b> <b>Height (H) x Width (W) x Depth (D)</b>	40mm x 208mm x 116mm
<b>Available Interface</b>	MPO to LC
<b>Fiber Count per Cassette</b>	72-Fiber per Cassette Options of 6x12F MPO-Male, or 3x24F MPO-Male
<b>Available Fiber Modes</b>	Singlemode (OS 1/2) Multimode (OM1, OM2, OM3, OM4)
<b>Color &amp; Coating</b>	Black Powder Coating
<b>Compliance</b>	RoHS
<b>Optional Preloaded Units</b>	MPO-Male Hydra Assemblies MPO Adapter (at the rear) LC Adapter (at the front) Channel Label and Data Label (printed on the front and rear)

# HD MPO CASSETTE MODULES

## PRELOADED WITH 6X12F MPO INTERFACE




Preloaded: 6pcs of 12-Fiber MPO to LC Hydra Assemblies  
72-Port LC Adapters at the Front  
6pcs of MPO Adapter at the Rear

Item Description			Part No. <sup>(1), (2)</sup>
Fiber Count Per Cassette	Fiber Mode	Color of LC Adapter	
72	OS1/OS2	Blue	HMC4S1D
72	OM1	Beige	HMC4M1D
72	OM2	Beige	HMC4M2D
72	OM3	Aqua	HMC4M3D
72	OM4	Aqua	HMC4M4D

(1) The above Part No. refer to using standard MPO connector, please contact Olabs support team when Low Loss MPO is required

(2) All plug-and-play cassette is pinned (Male), please contact Olabs support team when Non-pinned (Female) cassette is required

## PRELOADED WITH 3X24F MPO INTERFACE



Preloaded: 3pcs of 24-Fiber MPO to LC Hydra Assemblies  
72-Port LC Adapters at the Front  
3pcs of MPO Adapter at the Rear

Item Description			Part No. <sup>(1), (2)</sup>
Fiber Count Per Cassette	Fiber Mode	Color of LC Adapter	
72	OS1/OS2	Blue	HMC5S1D
72	OM1	Beige	HMC5M1D
72	OM2	Beige	HMC5M2D
72	OM3	Aqua	HMC5M3D
72	OM4	Aqua	HMC5M4D

(1) The above Part No. refer to using standard MPO connector, please contact Olabs support team when Low Loss MPO is required

(2) All plug-and-play cassette is pinned (Male), please contact Olabs support team when Non-pinned (Female) cassette is required