

Category	Rack enclosures																				
Specification	19" Rackmount Enclosure for Patching																				
<b>Parameters</b>	<p><b>Main Material :</b></p> <ul style="list-style-type: none"> <li>• Cold Rolled Steel</li> <li>• <i>Option for Aluminum</i></li> </ul> <p><b>Panel Type :</b></p> <ul style="list-style-type: none"> <li>• Modular Drawer Type (For 1U, 2U &amp; 4U)*               <ul style="list-style-type: none"> <li>* Option for 2U Panel :                   <ol style="list-style-type: none"> <li>1. Type-1 : Accommodate with 1 Drawer ( 2U height)</li> <li>2. Type-2 : Accommodate with 2 Drawers ( 1U height)</li> </ol> </li> </ul> </li> <li>• Traditional Fixed Type (For 4U only, with 12x vertical slot)*               <ul style="list-style-type: none"> <li>* Option for 2U Panel :                   <ol style="list-style-type: none"> <li>1. Type-1 : Accommodate with 155mm faceplate</li> <li>2. Type-2 : Accommodate with 120mm faceplate</li> </ol> </li> </ul> </li> </ul> <p><b>Dimensions :</b> Height (U) x Width (W) x Depth (D) in mm</p> <ul style="list-style-type: none"> <li>• 1U x 435mm x 380mm</li> <li>• 2U x 435mm x 380mm</li> <li>• 4U x 435mm x 380mm</li> </ul> <p><b>Interface :</b> FC, SC, ST, LC</p> <p><b>Fiber Count per Panel :</b> 12/24/48/72/96/144</p> <table border="1" data-bbox="455 1207 1279 1537"> <thead> <tr> <th>Height Interface</th> <th>1U</th> <th>2U</th> <th>4U</th> </tr> </thead> <tbody> <tr> <td><b>FC</b></td> <td>12- , 24-Fiber</td> <td>24- , 48-Fiber</td> <td>72- , 96- , 144-Fiber</td> </tr> <tr> <td><b>SC</b></td> <td>12- , 24-Fiber</td> <td>24- , 48-Fiber</td> <td>72- , 96- , 144-Fiber</td> </tr> <tr> <td><b>ST</b></td> <td>12- , 24-Fiber</td> <td>24- , 48-Fiber</td> <td>72- , 96- , 144-Fiber</td> </tr> <tr> <td><b>LC</b></td> <td>12- , 24- , 36- , 48- , 72-Fiber</td> <td>48- , 72-Fiber</td> <td>96- , 144-Fiber</td> </tr> </tbody> </table> <p><b>Available Fiber Mode :</b></p> <ul style="list-style-type: none"> <li>• Singlemode (OS 1/2)</li> <li>• Multimode (OM1, OM2, OM3, OM4)</li> </ul> <p><b>Compliance:</b> RoHS</p>	Height Interface	1U	2U	4U	<b>FC</b>	12- , 24-Fiber	24- , 48-Fiber	72- , 96- , 144-Fiber	<b>SC</b>	12- , 24-Fiber	24- , 48-Fiber	72- , 96- , 144-Fiber	<b>ST</b>	12- , 24-Fiber	24- , 48-Fiber	72- , 96- , 144-Fiber	<b>LC</b>	12- , 24- , 36- , 48- , 72-Fiber	48- , 72-Fiber	96- , 144-Fiber
Height Interface	1U	2U	4U																		
<b>FC</b>	12- , 24-Fiber	24- , 48-Fiber	72- , 96- , 144-Fiber																		
<b>SC</b>	12- , 24-Fiber	24- , 48-Fiber	72- , 96- , 144-Fiber																		
<b>ST</b>	12- , 24-Fiber	24- , 48-Fiber	72- , 96- , 144-Fiber																		
<b>LC</b>	12- , 24- , 36- , 48- , 72-Fiber	48- , 72-Fiber	96- , 144-Fiber																		

Specifications are subject to change without notice.

<b>Category</b>	<b>Rack enclosures</b>
<b>Specification</b>	<b>19" Rackmount Enclosure for Patching</b>
<b>Parameters</b>	<p><b>Coating and Color :</b></p> <ul style="list-style-type: none"> <li>• Black powder coating</li> </ul> <p><b>Preloaded Units :</b></p> <ol style="list-style-type: none"> <li>1. Adapter faceplate</li> <li>2. Cable management spool</li> <li>3. Adjustable Rackmount Ears, 70mm from the front plate (x 2pcs)</li> <li>4. Modular Drawer (For Drawer Type Only)</li> </ol>

Specifications are subject to change without notice.