

Category	Wallmount Panel																														
Specification	Indoor Wallmount Panel																														
Parameters	<p>Main Material : Cold Rolled Steel</p> <p>Dimensions: Height (H) x Width (W) x Depth (D) in mm • 400mm x 500mm x 200mm</p> <p>Support Applications : Patching / Splicing</p> <p>Interface : FC, SC, ST, LC</p> <p>Fiber Capacity per Panel : 12- / 24- / 36- / 48- / 96- / Fiber</p> <table border="1" data-bbox="439 749 1222 1085"> <thead> <tr> <th>Interface Fiber Count</th> <th>FC</th> <th>SC</th> <th>ST</th> <th>LC</th> </tr> </thead> <tbody> <tr> <td>12-Fiber</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> </tr> <tr> <td>24-Fiber</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> </tr> <tr> <td>36-Fiber</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> </tr> <tr> <td>48-Fiber</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> </tr> <tr> <td>96-Fiber</td> <td></td> <td></td> <td></td> <td>✓</td> </tr> </tbody> </table> <p>Available Fiber Mode :</p> <ul style="list-style-type: none"> • Singlemode (OS 1/2) • Multimode (OM1, OM2, OM3, OM4) <p>Compliance: RoHS , IEC 60529</p> <p>Ingress Protection : IP65</p> <p>Operating Temperature : -40°C to +60°C</p> <p>Coating and Color : Beige powder coating</p> <p>Preloaded Units :</p> <ol style="list-style-type: none"> 1. Adapter faceplate 2. Cable management spool 3. Door Lock and Key 4. Splicing kit (for Splicing only) 	Interface Fiber Count	FC	SC	ST	LC	12-Fiber	✓	✓	✓	✓	24-Fiber	✓	✓	✓	✓	36-Fiber	✓	✓	✓	✓	48-Fiber	✓	✓	✓	✓	96-Fiber				✓
Interface Fiber Count	FC	SC	ST	LC																											
12-Fiber	✓	✓	✓	✓																											
24-Fiber	✓	✓	✓	✓																											
36-Fiber	✓	✓	✓	✓																											
48-Fiber	✓	✓	✓	✓																											
96-Fiber				✓																											

Specifications are subject to change without notice.