

Category	Rack enclosures
Specification	19" High Density (HD) Rackmount Enclosure for 40G / 100G Ethernet
<b>Parameters</b>	<p><b>Main Material :</b></p> <ul style="list-style-type: none"> <li>• Cold Rolled Steel</li> <li>• <i>Option for Aluminum</i></li> </ul> <p><b>Panel Type :</b></p> <ul style="list-style-type: none"> <li>• Fixed Type</li> </ul> <p><b>Dimensions:</b> Height (U) x Width (W) x Depth (D) in mm</p> <ul style="list-style-type: none"> <li>• 1U x 435mm x 380mm</li> </ul> <p><b>Interface :</b> MPO-LC</p> <p><b>Fiber Count per Cassette:</b> 72-fiber (3x24 MPO-F or 6x12 MPO-F)</p> <p><b>Total Fiber Count per Panel :</b> 144-fiber</p> <p><b>Available Fiber Mode :</b></p> <ul style="list-style-type: none"> <li>• Singlemode (OS 1/2)</li> <li>• Multimode (OM1, OM2, OM3, OM4)</li> </ul> <p><b>Compliance :</b> RoHS , IEEE802.3ba</p> <p><b>Coating and Color :</b> Black powder coating</p> <p><b>Preloaded Units :</b></p> <ol style="list-style-type: none"> <li>1. MPO-LC Cassette (with MPO Hydra assemblies preloaded)</li> <li>2. Adjustable Rackmount Ears, 70mm from the front plate (x 2pcs)</li> </ol>

Specifications are subject to change without notice.