

Category	Rack enclosures								
Specification	19" Plug-and-Play Rackmount Enclosure								
Parameters	<p>Main Material :</p> <ul style="list-style-type: none"> • Cold Rolled Steel • Option for Aluminum <p>Panel Type :</p> <ul style="list-style-type: none"> • Modular Drawer Type (For 1U, 2U & 4U) • Fixed Type (For 4U only, with 12x vertical slots) <p>Dimensions: Height (U) x Width (W) x Depth (D) in mm</p> <ul style="list-style-type: none"> • 1U x 435mm x 380mm • 2U x 435mm x 380mm • 4U x 435mm x 380mm <p>Interface : MPO-LC</p> <p>Fiber Count per Cassette:</p> <ul style="list-style-type: none"> • 12-Fiber (1x12 MPO-F) • 24-Fiber (1x24 MPO-F or 2x12 MPO-F) <p>Fiber Count per Panel :</p> <ul style="list-style-type: none"> • Options of 36- / 48- / 72- / 96- / 144- / 192- / 288- / 384-Fiber <table border="1" data-bbox="501 1161 1296 1325"> <thead> <tr> <th>Height Interface</th> <th>1U</th> <th>2U</th> <th>4U</th> </tr> </thead> <tbody> <tr> <td>MPO-LC</td> <td>36-, 48-, 72-, 96-Fiber</td> <td>72-, 96-, 144-, 192-Fiber</td> <td>144-, 192, 288, 384-Fiber</td> </tr> </tbody> </table> <p>Available Fiber Mode : Singlemode (OS 1/2) Multimode (OM1, OM2, OM3, OM4)</p> <p>Compliance: RoHS</p> <p>Coating and Color : Black powder coating</p> <p>Preloaded Units :</p> <ol style="list-style-type: none"> 1. MPO-LC Cassette (with MPO Hydra assemblies preloaded) 2. Adjustable Rackmount Ears, 70mm from the front plate (x 2pcs) 3. Modular Drawer (For Drawer Type Only) 	Height Interface	1U	2U	4U	MPO-LC	36-, 48-, 72-, 96-Fiber	72-, 96-, 144-, 192-Fiber	144-, 192, 288, 384-Fiber
Height Interface	1U	2U	4U						
MPO-LC	36-, 48-, 72-, 96-Fiber	72-, 96-, 144-, 192-Fiber	144-, 192, 288, 384-Fiber						

Specifications are subject to change without notice.