

<b>Category</b>	<b>40G/100G Fiber Cabling System</b>															
<b>Specification</b>	<b>MPO Loopback for 40G/100G</b>															
<b>Parameters</b>	<p><b>Cable Type :</b> Bend Insensitive Cable</p> <p><b>Connector Type :</b></p> <ul style="list-style-type: none"> <li>• 12-Fiber Standard MPO Non-pinned</li> <li>• 24-Fiber Standard MPO Non-pinned</li> <li>• 12-Fiber Low Loss MPO Non-pinned</li> <li>• 24-Fiber Low Loss MPO Non-pinned</li> </ul> <p><b>Fiber Count Options :</b> 12-Fiber / 24-Fiber</p> <p><b>Available Fiber Mode :</b></p> <ul style="list-style-type: none"> <li>• Multimode (OM3, OM4)</li> </ul> <p><b>Optical Performance :</b></p> <table border="1" data-bbox="439 917 1222 1226"> <thead> <tr> <th><b>Fiber Mode</b></th> <th>Standard MPO Multimode</th> <th>Low Loss MPO Multimode</th> </tr> </thead> <tbody> <tr> <td><b>Parameters</b></td> <td></td> <td></td> </tr> <tr> <td><b>Test Wavelength</b></td> <td>850nm</td> <td>850nm</td> </tr> <tr> <td><b>Channel Loss</b></td> <td>≤ 1 dB</td> <td>≤ 0.6 dB</td> </tr> <tr> <td><b>Return Loss</b></td> <td>≥ 20dB</td> <td>≥ 20dB</td> </tr> </tbody> </table> <p><b>Compliance:</b> RoHS , IEEE802.3ba</p>	<b>Fiber Mode</b>	Standard MPO Multimode	Low Loss MPO Multimode	<b>Parameters</b>			<b>Test Wavelength</b>	850nm	850nm	<b>Channel Loss</b>	≤ 1 dB	≤ 0.6 dB	<b>Return Loss</b>	≥ 20dB	≥ 20dB
<b>Fiber Mode</b>	Standard MPO Multimode	Low Loss MPO Multimode														
<b>Parameters</b>																
<b>Test Wavelength</b>	850nm	850nm														
<b>Channel Loss</b>	≤ 1 dB	≤ 0.6 dB														
<b>Return Loss</b>	≥ 20dB	≥ 20dB														

Specifications are subject to change without notice.